

Microwave Sintering Lunar Landing Pads & Horizontal Infrastructure

Moon Village Architecture Working Group Workshop
December 14, 2020

Michael Effinger*

Moon to Mars Planetary Autonomous Construction Technology's (MMPACT)

Microwave Structure Construction Capability Element Lead

Special Thanks to these Contributors:

Lee Allen*, Curtis Bahr[†], Martin Barmatz**, Ralph Bruce***, Corky Clinton*, Jennifer Edmunson*, William Kaukler[†], Thomas Meek³, Savannah Metz*, Robert Mueller^t, Doug Rickman[†], Zack Roberts¹, Holly Shulman^φ, Laurent Sibille^t

*Marshall Space Flight Center, **Jet Propulsion Laboratory, ***RW Bruce Associates, LLC, [‡]Jacobs, ³The Crown College, ^½Kennedy Space Center, ^¼Radiance Technologies, ^φDr Holly Shulman Sole Proprietorship

Agenda



- Overview
- Technical Challenges
- Current status
- Forward Work
- Summary

race

Microwave Structure Construction Capability (MSCC) Overview



Goals


- Mature the technology and capability to emplace in-situ-based construction materials on the Moon to form infrastructure elements (horizontal infrastructure, e.g., landing pads, roads, etc.)
- Develop and demonstrate microwave sintering of lunar simulants that can be used to form infrastructure on the Moon for a mid-sized payload (e.g., 2mT microwave paver vehicle)

Objectives

- Develop microwave sintering protocols/processes and horn/applicator designs
- Demonstrate microwave sintering construction of subscale structures

MSCC Team Partners





acc frac



ConOps

 Initial system concept of operations (ConOps) definition that have high specific area sintered/power in reasonable time with functional simplicity and robustness

Simulant & Synthetic Minerals

- The number of variables in the lunar regolith that might affect microwave absorption characteristics & resulting ceramic properties is very large (e.g., distributions of particle size, shape, composition, etc.)
- Simulants needed to perform the necessary tests are too limited in specifications and availability
- Parameter space can not be explored directly and definitively via large scale experiments
- Lack of lunar highland type and other simulants



Site Prep

- Terrain surveying in high light contrast conditions
- Lunar regolith typically compacts less than terrestrial simulants, with larger void ratios
- Degree of uniformity of prepared regolith layers to meet microwave sintering requirements
- Dust generation during site preparation may lead to navigation, positioning errors and consequently construction errors

Design

- System that can survive lunar night
- Accurate temperature dependence of lunar simulant permittivity and other physical parameters (thermal conductivity and specific heat)

COCC.

- Thermal management system for paver vehicle
- Power available with respect to construction time
- Design of a applicator that can work continuously in a lunar environment while exposed to an 1100C radiant surface and volatiles



Microwave Sintering

- Regolith is a super insulator that prevents conduction of heat from the surface
- Develop accurate method for determining temperature when sintering takes place for ground testing
- Gain understanding of the heating profile and depth of penetration of the microwaves into the regolith
- Development of procedures for applicator such that it can withstand the heat and volatile generation without significant degradation
- Determine (and develop optimized energy efficient process) mass sintered simulant densified per hour with magnetron from -200C to sintering temperature, accounting for porosity, and mitigating thermal runaway



Testing

Obtaining vacuum capability for certain testing (e.g., thermal & mechanical properties)

Ancillary Instruments

- Ceramic product verification with non-uniform porosity, thickness, and graded density
- High temperature measurement of off-gas products from a sintering operation



(20 ft. diameter x 28 ft. long), Existing vacuum chamber system

Credit: NASA




2006 1kW microwave heater before vacuum chamber testing Credit: NASA

Current Status



- Three contracts awarded
- Building up and activating microwave sintering testing facilities at Alfred University, JPL, Radiance Technologies & MSFC
- Initiated simulant heating modeling using HFSS and COMSOL (JPL, Space Resources Extraction Technologies, & MSFC)

Initiated microwave sintering vehicle conceptual design



4' diameter TVAC chamber with microwave

Credit NASA

Forward Work



- Known Gaps
 - Generating process monitoring instrumentation
- Forward leveraging planned
 - Flight site preparation vehicle (rock removal, leveling, etc.)
 - Tailor mass spectrometer and other existing flight volatile identification systems to MSCC needs
 - Tailor microwave radiometer and/or thermography for temperature measurements
 - Tailor terrain mapping and applicator positioning instruments
- Solar power amplification and transmission to solar cells
- Flight microwave sintering vehicle PDR, CDR, fabrication, assembly, testing, software, automation, con-ops, mobility system, guidance navigation and control, and delivery
- Not required to complete paving job, but useful for increased lunar human sustainability
 - Integration of any volatile collecting systems from OTHER projects (likely on 2nd generation paver)


Corec.

- Apply principles to the beneficiation/extraction of minerals and other lunar resources
- Apply principles to vertical structure fabrication

Summary



- MSCC is a broad & deep industry, academia, and multi-NASA Center team with extensive microwave and site preparation experience that will enable TRL 6 achievement for process and hardware that will ultimately yield a microwave sintered landing pad on the Moon
- MSCC has multiple design and testing paths to achieve optimal solution (i.e., competition within)
- MSCC has two design and test cycles for multiple technologies (i.e., design, test, incorporate lessons learned in redesign)
- MSCC is developing some ancillary technology necessary to enable landing pad fabrication (i.e., site preparation, volatile characterization on ground, & ceramic landing pad in-situ verification)



www.nasa.gov